



CR 150x210x220

Jelentkezz be az árak megtekintéséhez

Cold Room Panels 80 mm

- Only panels – without cooling unit
- Interlocking connection system
- 80 mm panel insulation
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access

Cold room panels with 80 mm insulation

Our range of cold room panels are available with 80 mm or 120 mm of effective polyurethane insulation and comes in various sizes. They have an easy interlocking system which makes assembly quick and hassle-free. The modular panels are interchangeable, so you can move the position of the door and adapt the room to fit your needs. Monoblock refrigeration units can be ordered separately.
Incl. spareparts 1 year

Paraméterek:

Gross / Net Weight	241 / 221 kg
Gross / Net Volume	5300 l
Internal Volume	5.3 m ³
Wall Thickness	80 mm
Insulation Density	42 kg/m ³
Door No & Type	1 hinged solid door
Door Reversible	Yes
Exterior Finish	White
Interior Finish	White
Lock	Yes
Max Load on Floor	1500 kg/m ²
Energy Consumption	0 kWh/24h
Annual Energy Cons.	0 kWh/year
Internal Dimension (WxDxH)	1340 x 1940 x 2040 mm
External Dimension (WxDxH)	1500 x 2100 x 2200 mm
Packed Dimension (WxDxH)	2180 x 1280 x 1200 mm
40ft Container Load	16 pcs



VTSZ: 8418